



T-Fresh Floor Standing Heat Pumps





Find out more at www.greeac.co.nz

Gree T-Fresh Floor Standing Heat Pumps

Side-drawing filter design for convenient cleaning*

The filter adopts user-friendly side-drawing design, which is more convenient for cleaning.



Fully-closed air outlet

The air outlet can be completely closed to avoid dust from entering, safeguarding the health of your family.



Туре		T-Fresh
Model	Ind	GVH32ALXH-K6DNC7A/I
	Out	GVH32ALXH-K6DNB2A/O
Performance		
Cooling Capacity (Range)	kW	10.0
Heating Capacity (Range)	kW	10.3
Cooling Power Input	kW	2.73
Heating Power Input	kW	3.02
Cooling EER	W/W	3.66
Heating COP	W/W	3.4
Dehumidifying Volume	L/Hr	5.0
Air Flow Volume (Max)	L/Sec	361~514
Sound Pressure (Min/Max) Ind	dB(A)	47~52
Power Supply (Outdoor)	V/Hz/Ph	220~240/50/1
Recommended Circuit Breaker	А	25
Nominal Current (Cool / Heat)	А	11.5/13.5
Control Wiring		4 Core
Indoor Dimensions (WxHxD)	mm	587 x 1882 x 394
Indoor Net Weight	kg	57
Outdoor Dimensions (WxHxD)	mm	1000 x 746 x 427
Outdoor Net Weight	kg	59.5
Operating Temp Range Cool	°C	-10° ~ 50°
Operating Temp Range Heat	°C	-15° ~ 24°
Refrigerant Type		R32
Refrigerant Charge	kg	1.9
Max Pipe Length (pre-charged)	М	25 (10)
Max height		10
Additional Refrigerant	g/m	40
Pipe Connection		1/4" ~ 5/8"

Features



Dehumidifying



Normal Sleep





Auto Swing





Eco Mode



Power-Off Memory



Intelligent Defrosting



Self-Diagnosis



Turbo Button



Soft Start



Low-Voltage Startup



Closed Louver Design



Intelligent Preheating



Dry Anti-Midew **Technology**



LED Display



Lock





Wifi Control Nano-Cataylistic





Optional